

Truncated Setting Plug Gages



**Class "X" Pitch Diameters
"W" Lead & Angles
Precision Lapped**

NOMINAL SIZE	THREADS PER INCH			MEMBERS		HANDLES		DOUBLE END
	NC UNC	NF UNF	NEF UNEF	GO	NO GO	NO.	PRICE	2A, 3A
				2, 3 1A, 2A, 3A	2A, 3A			
0		80		96.00	96.00	000	11.00	203.00
1	64	72		96.00	96.00	000	11.00	203.00
2	56	64		96.00	96.00	000	11.00	203.00
3	48	56		87.00	87.00	000	11.00	185.00
4	40	48		87.00	87.00	00	11.00	185.00
5	40	44		82.00	82.00	00	11.00	175.00
6	32	40		82.00	82.00	00	11.00	175.00
8	32	36		82.00	82.00	0	11.00	175.00
10	24	32		82.00	82.00	0	11.00	175.00
12	24	28		87.00	87.00	0	11.00	185.00
12			32	106.00	106.00	0	11.00	223.00
1/4	20	28		75.00	75.00	1	11.00	161.00
1/4			32	109.00	109.00	1	11.00	229.00
5/16	18	24		75.00	75.00	1	11.00	161.00
5/16			32	109.00	109.00	1	11.00	229.00
3/8	16	24		79.00	79.00	2	11.00	169.00
3/8			32	122.00	122.00	2	11.00	255.00
7/16	14	20		82.00	82.00	2	11.00	175.00
7/16			28	124.00	124.00	2	11.00	259.00
1/2	13	20		84.00	84.00	2	11.00	179.00
1/2			28	135.00	135.00	2	11.00	281.00
9/16	12	18		96.00	96.00	3	11.00	203.00
9/16			24	145.00	145.00	3	11.00	301.00
5/8	11	18		100.00	100.00	3	11.00	211.00
5/8			24	150.00	150.00	3	11.00	311.00
11/16			24	160.00	160.00	3	11.00	331.00
3/4	10	16		116.00	116.00	3	11.00	243.00
3/4			20	158.00	158.00	3	11.00	327.00
13/16			20	165.00	165.00	3	11.00	341.00
7/8	9	14		134.00	134.00	4	12.00	280.00
7/8			20	168.00	168.00	4	12.00	348.00
15/16			20	170.00	170.00	4	12.00	352.00
1"	8	12	14NS	154.00	154.00	4	12.00	320.00
1"			20	178.00	178.00	4	12.00	368.00
1-1/16		12	18	174.00	174.00	4	12.00	360.00
1-1/8	7	12		174.00	174.00	4	12.00	360.00
1-1/8			18	186.00	186.00	4	12.00	384.00
1-3/16		12	18	183.00	183.00	5	13.00	379.00
1-1/4	7	12		190.00	190.00	5	13.00	393.00
1-1/4			18	218.00	218.00	5	13.00	449.00
1-5/16		12	18	219.00	219.00	5	13.00	451.00
1-3/8	6	12		220.00	220.00	5	13.00	453.00
1-3/8			18	230.00	230.00	5	13.00	473.00
1-7/16		12	18	232.00	232.00	5	13.00	477.00
1-1/2	6	12		235.00	235.00	5	13.00	483.00
1-1/2			18	245.00	245.00	5	13.00	503.00

For class "W" pitch diameters – add 25%.